



## TEX - Wallpaper Remover

For the easy removal of normal wallpapers, distemper and smear-resistant emulsion paint.

Scope of application:	The new active substance peels off all wallpapers quickly and securely without any pre-treatment. Specific additives ensure an even wetting without the liquid draining.
Properties:	In powder form. When mixing the product it becomes a foam-like structure = thus no draining on the wallpaper. Extremely high effectiveness = short reaction time
Technical specifications:	Raw material base: Prepared from anionic and non-anionic surfactants, phosphate and additives.  Make-up ratio: 100 g of the product into 10 - 15 l water  Consumption: 100 g TEX Wallpaper Remover are sufficient for 100 to 150 m <sup>2</sup>
Processing:	Dissolve Tex Wallpaper Remover in 10 to 15 l warm water and stir until foamy. Use a ceiling brush, sponge or garden irrigation nozzle to apply the remover generously in running direction of the wallpaper. Allow it to react for 10 to 15 minutes. Repeat the procedure, if required. After this, remove the wallpaper strip by strip.  Always clean the tools thoroughly with water immediately after use.
Identification:	Please refer to the EC safety data sheet for the pertinent information.
Storage property:	Store the product in a cool, dark and dry place.
Other:	Always read the label and product information before use.  Use warm or hot water to increase the effect.  Water-repellent wallpapers must be roughened with a spiked roller before applying the liquid.
Package sizes:	Folding box with 100 g Folding box with 200 g Folding box with 1 kg