



Cement Film Remover and Descaling Agent

Highly effective acid cleaning concentrate for acid-resistant substrates.

Scope of application:	For the easy cleaning and removal of lime and cement films, inorganic soiling and flash rust, also in connection with oily and greasy dirt. Appropriate for the cleaning of acid-resistant substrates, such as wall and floor tiles, clinker and brick areas, porcelain stoneware in sanitary facilities, swimming pools, kitchens, car wash buildings, brick fronts. Before using on bathroom fittings, always check for compatibility.
Properties:	Degreasing, with excellent dirt-dissolving properties.
Technical specifications:	Raw material base: Aqueous solution consisting of surfactants, alcohol and formic acid Make-up ratio: depending on the soiling 1:1 to 1:15 Consumption: 100 - 120 ml/m ² prepared stock solution
Processing:	Depending on the dirt, dilute with water to a ratio of 1:1 to 1:15. Spray the solution onto the dirt, or apply it with a sponge or scrubbing brush. Allow it to react for 10 to 15 minutes, after this rewash with clear water. In case of strongly porous surfaces, we recommend to pre-wet the area. Joint areas must be always pre-wetted before applying the remover. Always clean the tools thoroughly with water immediately after use.
Identification:	Please refer to the EC safety data sheet for the pertinent information.
Storage property:	Store the product in a cool, dark and dry place.
Other:	Always read the label and product information before use. Caution: The application of the solution on acid-sensitive surfaces may lead to irreversible damage. Always check the surface compatibility before use.
Container sizes:	Bottle with 1,000 ml Jerrican with 5 l Jerrican with 10 l