



## Industrial Cleaning Agent

The special cleaning agent for industry and workshop use

**Scope of application:** The product dissolves grease, oil from contaminated workshop floors, machines and machine parts, sanitary facilities, floors and etc. Greasy floors become slip-resistant as soon as the floor has dried.

**Properties:** Degreasing, with excellent dirt releasing properties, non-corrosive

**Technical specifications:** Raw material aqueous alkaline solution containing anionic and non-base: anionic surfactants, phosphate and additive substances

**Make-up ratio:** depending on the degree of soiling 1:1 to 1:20

**Consumption:** 100 - 120 ml/m<sup>2</sup> of prepared stock solution

**Processing:** Dilute with water, depending on the degree of soiling in ratio 1:1 to 1:20. Spray the product on the dirt or use a sponge or ceiling brush for applying. Rewash with clear water after a reaction time of 20 to 30 minutes..

Always clean the tools thoroughly with water immediately after use.

**Identification:** Please refer to the EC safety data sheet for the pertinent information.

**Storage property:** Store the product in a cool, dark and dry place.

**Other:** Always read the label and product information before use.

Industrial cleaning agents can also be used in machine halls to clean the floors.

**Container sizes:** Bottle with 1,000 ml  
Jerrican with 5 l  
Jerrican with 10 l