



Isospray White

Isolation and sealing primer for inside and outside, white pigmented

Scope of application: For the rapid isolation of water stains, nicotine, tar and soot, smoke spots, asphalt, carbolineum, bitumen and colour pencils. The product can be applied on many critical substrates, such as mineral substrates, wood-based material, and styrofoam (polystyrene).

Properties: A universal isolation and sealing product for inside and outside that may be equally applied on styrofoam (polystyrene), wood-based material and cardboard;
rapid dry time = can be coated within a short time;
extremely high sealing effect ;
for inside and outside;
free of aromatic compounds

Technical specifications: Raw material base: Preparation based on synthetic resins, organic solvents and pigments.

Make-up ratio: undiluted

Consumption: 400 ml for 2-3 m²

Processing: The substrate must be dry, clean and load-bearing. (We recommend Geiger Leach Agent SE-1 to achieve this). Stir the material well before processing. It is preferable to apply the material by spraying or rolling. Make sure that the temperature during the whole processing and drying period is in the range of at least 8°C and maximally 30°C. One to two coatings must be applied in order to ensure the optimum isolation effect. After a drying time of 60 to 90 minutes the material can be painted over (does not apply to 2K-materials).

Always clean the tools thoroughly with water immediately after use.

Identification: Please refer to the EC safety data sheet for the pertinent information.

Storage property: Store the product in a cool, dark and dry place.

Other: Always read the label and product information before use.

It is good practice to test the isolation effect at an unobtrusive point.

Container sizes: Aerosol can with 400 ml